

Sky Pro Mini Sprayer is a touchless window and facade cleaning system ideal for buildings up to 15 stories. This system uses a technology similar to a touchless carwash with a 3.5 ft (1.1m) cleaning path from a distance up to 3 feet. The Sky Pro Mini Sprayer is suitable for buildings with irregular windows, offsets or insets, curves, recesses, overhangs, protrusions, asymmetrical frames or other architectural features that make traditional cleaning methods difficult, if not impossible. Optional guideline kit provides more stability for taller buildings or windy conditions.



Inside View of Sprayer

The Sky Pro Mini Sprayer **BASE PACKAGE** includes:

- Heavy duty white polypropylene shell
- 2 wind stabilizer arms with foam end to protect building
- Water spinner bar with 2 rotary nozzles and 2 fan tip nozzles
- Rear mounted water pressure gauge
- Waste water evacuation tube on bottom of Mini Sprayer
- Regulator valve to control and conserve water consumption
- Lifting shackle and cable support grip
- High performance pressure washer with built in hose reel including 50 ft of high pressure water hose. Additional 150 ft of high pressure water hose is included
- Spray wand
- Adjustable rolling outrigger with 5 counterweights
- 115V/220V amps variable speed hoist with limit switch, 180 ft of air craft galvanized wire rope, drum guard, "up/down" pendant and waterproof dust cover
- 1 year parts warranty

Sky Pro Mini Sprayer **OPTIONS:**

- R.O./D.I. water filtration unit for "spot free" windows
- Rolling parapet wall clamp outrigger
- Enclosed Titan trailer with ramp and side door
- Custom decals for trailer
- Back-up second safety cable - Self-Retracting Lifeline (SRL)
- Customized parts, chemical injector, hot water heater, mobile generator, or equipment transport trailer
- Guide lines kit
- Spare parts kit


Sky Pro Mini Sprayer **SPECS**

	Standard	Metric
Pressure Washer	62 lbs.	28 kg.
Water Pressure	900-1200 psi	4.8 -6.9 MPa
Water Consumption	2.4 gpm	9.085 l/m
Frequency (Pressure Washer)	50 V 60 Hz	50 V 60 Hz
Voltage (Pressure Washer)	115/220V	115/220V
Hoist Speed- Variable	22-34 ft/min	0.11-0.17 m/s
Number of Nozzles	2 (a)	2 (a)
Voltage (Hoist)	115/220V	115/220V
Circuit Breaker Size (Hoist)	15 amps (b)	15 amps (b)
Frequency (Hoist)	50 or 60 Hz	50 or 60 Hz
Weight	83 lbs.	38 kg

**** Please note the letters in parentheses reflect the key below.**

- (a) 4 nozzles - comes with 2 rotary and 2 fan tips which are interchangeable.
- (b) Electrical required for rooftop hoist

Winch



Rolling Outrigger



High Performance
Water Pump



High Pressure
Water Hose

