# ky Pro<sup>®</sup> Brush Machine

World Leader in Automated Window & Facade Cleaning Technology

Patented



Metric

## **Sky Pro Brush Machine**

is a window and facade cleaning system ideal for buildings up to 60 stories. This system uses technology similar to a soft touch foam brush carwash with an 8 ft (2.4m) cleaning path. The Brush Machine is suitable for buildings with flat glass facades and windows inset no more than 4 inches. Two rear mounted fans to keep machine against building.



#### The Sky Pro Brush Machine **BASE PACKAGE** includes:

- Rotating foam brush specially designed to clean windows, window frames, and building exterior
- 2 rear mounted fans to keep machine against building
- 2 brush motors to ensure consistent torque and rotation speed
- 1 side brush to clean in corners of building and have a larger cleaning path
- Aluminum, powder coated frame
- Removable swivel wheels mounted on bottom of frame for easy transport
- Splash guard to minimize overspray
- Stainless steel water distribution system
- Regulator valve to control water consumption
- 2 balloon tires on frame to protect building
- Electrical control box and 500 ft of electrical cable
- 350 ft of 5/16 inch galvanized wire rope
- 400 ft of 3/8 inch water hose
- Full remote control (fans, water, and brush forward/reverse control)
- 1 year parts warranty

#### Sky Pro Brush Machine OPTIONS:

- Rooftop outrigger with counterweights
- Rolling parapet wall outrigger
- Mobile davit outrigger with counterweights
- R.O./D.I. water filtration unit for "spot free" windows
- Wire winder; 500 ft maximum (mounts on rooftop outrigger)
- Self-climbing option (emergency release system, rope not included)
- Hand crank reels for water hose and cable management
- Customized parts, chemical injector, hot water heater, mobile generator, and equipment transport trailers.
- Enclosed trailer
- Spare parts kit

### Sky Pro Brush Machine SPECS Standard

Water Pressure	50-80 psi	207-552 kPa
Water Consumption	2.4 GPM	9.1 LPM
Number of Nozzles	8	8
Voltage	220/230 V	220/230 V
Frequency	50 or 60 Hz	50 or 60 Hz
Weight	480 lbs (a)	218 kg <mark>(a)</mark>

\*\* Please note the letters in parentheses reflect the key below.
(a) Doesn't include weight of hoist, variable speed box, water hose, or electrical cable

#### **Optional Outrigger**

